

TBC 600-1 kanaals

TBC 612-1-15 TBC 612-1-25 TBC 612-1-35 TBC 612-1-50 TBC 624-1-10 TBC 624-1-20 TBC 624-1-30 TBC 624-1-40

Ingangsspanning <i>Input Voltage</i>	230VAC 115VAC	180 - 240VAC, 50/60Hz 95 - 125VAC, 50/60Hz							
Uitgangsspanning (nominaal) <i>Output voltage (nominal)</i>	12VDC				24VDC				
Inschakelspanning <i>Active battery Voltage</i>	≥ 1 Volt								
Laadkarakteristiek <i>Charge curve</i>	IUoUoe / IUlaoUoe								
Max. laadstroom <i>Maximum charge current</i>	15 Amp.	25 Amp.	35 Amp.	50 Amp.	10 Amp.	20 Amp.	30 Amp.	40 Amp.	
Max. lichtnetbelasting <i>Max. lighting load</i>	230VAC 115VAC	1,8 Amp. 3,7 Amp.	2,6 Amp. 6,1 Amp.	3,8 Amp. 8,3 Amp.	5,5 Amp. 12,3 Amp.	2,5 Amp. 5,3 Amp.	4,4 Amp. 10 Amp.	6,6 Amp. 14,5 Amp.	8,6 Amp. 19,7 Amp.
Ideale omgevingstemperatuur <i>Ideal working temperature</i>	5-20°C								
Beveiligingen <i>Protections</i>	Ompoling, kortsluiting (uitgang), temperatuur, ingangsspanning, stroombegrenzing <i>Reverse polarisation, short circuit, temperature, inputvoltage, current limitation</i>								
Max. luchtvochtigheid <i>Max. relative humidity</i>	90%								
Koeling <i>Ventilation</i>	Mechanisch <i>Mechanical</i>								
Batterij aansluiting <i>Battery connection</i>	M6 bouten (messing nikkel) <i>M6 bolts (brass nickel)</i>								
Soft start <i>Soft start</i>	Primair en secundair <i>Primary and secondary</i>								
Galvanisch gescheiden <i>Galvanic separated</i>	Ja Yes								
Behuizing <i>Housing</i>	Aluminium <i>Aluminium</i>								
Beschermingsgraad (EMC) <i>Level of protection (EMC)</i>	IP 647								
Afmetingen (lxbxh in cm) <i>Dimensions (lxwxh cm)</i>	20x20x11	25x20x11	30x20x11	40x20x11	20x20x11	25x20x11	30x20x11	40x20x11	
Gewicht (kg) <i>Weight (kg)</i>	6	9	9	14	7	9	10	16	